

CLAIM LISTING

1. (Original) A plug receptacle premold which comprises:
a rigid plastic housing,
said housing comprising first and second contact pin holes, and
first and second contact pins,
at least one of said pins having male-blade-spaced portions at one end and
at the other end cooperative valving and seating portions.
2. (Original) The premold of claim 1 in which said portions are arranged for
resilient biasing toward each other.
3. (Original) A plug receptacle premold which comprises:
a rigid plastic housing,
said housing comprising first and second contact pin holes, and
first and second contact pins,
said pins having male-blade-spaced portions at one end and at the other
end cooperative valving and seating portions.
4. (Original) The premold of claim 3 in which said valving portion is a tongue
and said seating portion is a notch.
5. (Original) The premold of claim 1 which also includes a ground pin
receptacle,
said receptacle including a longitudinal embossment adapted to facilitate use
therewith of a round ground pin.

6. (Original) The premold of claim 1 which also includes a ground pin receptacle, said receptacle including a circumferential rib and a longitudinal gap.

7. (Cancelled).

8. (Cancelled).

9. (Currently amended) ~~The element of claim 8~~ A contact element for restricting flow of overmold into said element which comprises:

a body portion and

a valving portion,

said valving portion in use restricting said flow,

in which said element includes also a seating portion.

10. (Previously presented) The element of claim 9 in which said body portion is a longitudinally intermediately folded integral unit thin relative to its transverse width and including a blade-receptive slot extending from the fold at said folded location inwardly thereof,

said slot being correspondingly sized and oriented with respect to each body portion from said fold, each said body portion being spaced from the other suitably to jointly provide a female contact for a male plug blade,

and which also includes a valve portion and a seat portion, at facing ends of said body portion away from said fold.

11. (Currently amended) The element of claim ~~[[8]]~~ 9 in which said valving portion is carried by said body portion.

12. (Previously presented) The element of claim 11 in which said body portion is the annulus of a cylinder in cross-section and said valving portion is a peripheral rib extending outwardly thereof, said body portion including a longitudinal split.

13. (Cancelled).